



**NOTES:**  
 1: 3/8" TUBING LINE IS INSIDE 3/4" CONDUIT LINE UNDER VESSEL INSULATION  
 2: SPOOL FOR OPTIONAL 2" CL150 DANIEL SENIOR METER RUN

**FABS-100**  
**BURNER/FIRED HEATER**  
 TYPE: SINGLE BURNER  
 RATING: 1.0 MM BTUH

**V-100**  
**NATCO TREATER (RECONDITIONED)**  
 72" ID x 20'-0" S/S  
 MAWP: 50 PSIG AT 5°F/250° F

**V-200**  
**FUEL GAS SCRUBBER**  
 10" OD x 28" S/S  
 MAWP: 150 PSIG AT -20°F/200° F

**BH-400**  
**BUILDING HEATER**  
 CATADYNE 12"x24"(12V), MK SERIES,  
 NATURAL GAS w/30' CABLES  
 ELECTRICAL PERMIT/REGULATOR/  
 SAFETY SHUTOFF/THERMOSTAT

NO.	DATE	REVISION	BY	APP
2	15-09-14	ADDED ANO-100		LDG
1	15-08-15	ADJUSTED V-200/ADDED THD BALL VALVE DRAINS		LDG
0	15-08-07	ISSUED FOR CONSTRUCTION		LDG

**NRG PROCESS SOLUTIONS**  
 #261185 WAGON WHEEL WAY. ROCKYVIEW COUNTY, AB  
 TELEPHONE: (403) 945-3561 EMAIL: SALES@NRGPS.CA

CLIENT:	STOCK
DATE:	14-10-29
BDD NO.:	
JOB NO.:	CES-412
SCALE:	NTS
DRAWN BY:	LDG
CHECKED BY:	TC

<b>72" x 20' TREATER</b>	<b>PROCESS AND INSTRUMENTATION DIAGRAM</b>	
	DWG NO.:	REV
CES-412 PID		2